



# GEORATOR Corporation

9617 Center Street  
 Manassas, Virginia 20110  
 U.S.A.

1-800-523-9938 toll free in USA  
 +1 703-368-2101  
 +1 703-368-1078 fax

[WWW.GEORATOR.COM](http://WWW.GEORATOR.COM)

MODEL 3 Phase Without Isolation Transformer	T3AVR-33-10K	T3AVR-33-15K	T3AVR-33-20K	T3AVR-33-25K	T3AVR-33-30K	T3AVR-33-50K	T3AVR-33-100K	T3AVR-33-150K
Capacity (KVA)	10	15	20	25	30	50	100	150
Dimenions (W*D*H in.)	14.2*21.3*22.5			16.2*31.1*28.0		20.9*40.2*32.3	23.6*47.3*52.0	31.5*47.3*57.9
Net Weight (lbs)	117	210	265	331	397	629	1389	2051
MODEL 3 Phase With Isolation Transformer	T3AVRI-33-10K	T3AVRI-33-15K	T3AVRI-33-20K	T3AVRI-33-25K	T3AVRI-33-30K	T3AVRI-33-50K	T3AVRI-33-100K	T3AVRI-33-150K
Capacity (KVA)	10	15	20	25	30	50	100	150
Dimenions (W*D*H in.)	14.2*21.3*38.2			16.2*31.1*47.3		23.6*44.1*52.0		31.5*47.3*65.8
Net Weight (lbs)	342	441	552	596	739	1213	2492	3638
Input Voltage Range	+/-15% (Option: +/-20% to +/-30%)							
Output Voltage Regulation	<=1%							
Frequency	50/60Hz +/-5%							
Power Factor	0.95 to 1							
Efficiency	>= 98% AC to AC Efficiency							
Distortion	/1% added to input distortion							
Response Time	0.1 Seconds, Sinusoidal Waveform							
Overload Capacity	150% for 10 seconds							
PROTECTION	Over Voltage	Limits Set by User; LED Display						
	Under Voltage	Limits Set by User; LED Display						
	Phase Failure	Limits Set by User; LED Display						
	Bypass	Limits Set by User; LED Display						
	Overload	Standard						
INDICATORS	Output Voltage Status	Standard						
	Output Voltage Power ON	Standard						
	Abnormal	Standard						
	Voltmeter	Standard						
	Ammeter	Standard						
Environment	0°C to 45°C, 0 to 95% Humidity (non Condensing)							

All specifications are subject to change without prior notice.