



The Frequency Converter People Since 1950

GEORATOR Corporation

9617 Center Street
Manassas, VA 20110

800 523-9938

703 368-2101

Fax: 703 368-1078

E-Mail: sales@georator.com

| Triathlon III UPS Specifications - 1 Phase Input to 3 Phase Output Model, 15 KVA | | |
|---|--|---|
| Model | T3UPS-13-15K | |
| Capacity | 15 KVA | |
| Input | Voltage (select one individual voltage) | 1 Phase 100, 110, 115, 120, 200, 208, 220, 230, or 240V ± 20% |
| | Frequency (select one) | 50 or 60 Hz ± 5% (Optional 400Hz) |
| | Power Walk In | 0-100%: 20 seconds |
| Output | Voltage (select one individual voltage) | 3 Phase Delta 220/380/460V (+/-5% adjustable)3 Phase Wye 190/200/208/220/230/240V (+/-5% adjustable)3 Phase Wye 380/400/415/440/460/480V (+/-5% adjustable) |
| | Voltage Regulation | ± 1% at Linear Load |
| | Phase Shift (unbal. load) | < 0.5 Deg. |
| | Frequency (select one) | 50 or 60Hz ±0.1 Hz (Optional 400 Hz) |
| | Power Factor | 0.8 |
| | Distortion (THD) | < 2.0% (Linear Load) |
| | Crest Factor | 3:1 |
| | Overload Capacity | 125% for 15 Minutes, 150% for 10 Minutes, > 150% for 1 Minute |
| | Efficiency | >= 93% |
| Indicators | LCD | Real Time Status, Data or Historical Events, Parameters, Real Time Clock, Inverter & Alarm |
| | LED | Up to date information (Status) to the User & Audible Alarm |
| Protection | Over/Under Voltage | Alarm |
| | Output Short Circuit | Auto-shutdown |
| | Overload | Auto-shutdown 25 sec. later |
| | Over Temperature | Auto-shutdown |
| | Lightning / EMC Filter | Surge and Lightning Protection |
| | EMI/EMC | EN50091-2 Approved |
| | Galvanic Isolation | Input & Output True Galvanic Isolation |
| Standards | FCC Class A | YES |
| | EN50091-1, -2 | YES |
| Interface | Contact Closure, RS-232/485 | Supports MEGATEC RUP, MEGATEC RUPSII, UPSilon 2000 UPS monitoring software |
| Environment | Operating Temperature | 0° – 40° C |
| | Humidity | 0 - 90% Non-condensing |
| | Audible Noise | < 65 dB at 1 meter |
| Dimensions | W x H x D (mm) | 550*1,600*800 |
| | W x H x D (in) | 21.7*63.0*31.5 |
| Weight * | Kilograms | 380.0 |
| | Pounds | 837.8 |
| Battery Weight | Kilograms | 85.0 |
| | Pounds | 188.5 |
| Battery | Type - Quantity | HR1234W - 58 ea. |
| Backup Time ** | Minutes - Minimum | 15 min. |

* Weights based on 220/380V IN and OUT. Weights may vary based on input/output frequency/voltage

** Longer backup times (to 8 hours) are available from standard models; custom specifications also available.