



The Frequency Converter People Since 1950

# GEORATOR Corporation

9617 Center Street  
Manassas, VA 20110

800 523-9938

703 368-2101

Fax: 703 368-1078

E-Mail: sales@georator.com

<b>Triathlon III UPS Specifications - 3 Phase Input to 1 Phase Output Model, 60 KVA</b>		
<b>Model</b>		<b>T3UPS-31-60K</b>
<b>Capacity</b>		60 KVA
<b>Input</b>	Voltage (select one individual voltage)	3 Phase Delta 220/380/460 ± 20% 3 Phase Wye 190/200/208/220/230/240V ± 20% Phase Wye 380/400/415/440/460/480V ± 20%
	Frequency (select one)	50 or 60 Hz ± 5% (Optional 400Hz)
	Power Factor	≥ 0.97
	Power Walk In	0-100%: 20 seconds
<b>Output</b>	Voltage (select one individual voltage)	100, 110, 115, 120, 200, 208, 220, 230, or 240V ( ± 5% adjustable)
	Voltage Regulation	± 1% at Linear Load
	Phase Shift (unbal. load)	< 0.5 Deg.
	Frequency (select one)	50 or 60Hz ±0.1 Hz (Optional 400 Hz)
	Power Factor	0.8
	Distortion (THD)	< 2.0% (Linear Load)
	Crest Factor	3:1
	Overload Capacity	125% for 15 Minutes, 150% for 10 Minutes, > 150% for 1 Minute
<b>Indicators</b>	Efficiency	≥ 91%
	LCD	Real Time Status, Data or Historical Events, Parameters, Real Time Clock, Inverter & Alarm
<b>Protection</b>	LED	Up to date information (Status) to the User & Audible Alarm
	Over/Under Voltage	Alarm
	Output Short Circuit	Auto-shutdown
	Overload	Auto-shutdown 25 sec. later
	Over Temperature	Auto-shutdown
	Surge	Surge and Lightning Protection
<b>Interface</b>	EMI/EMC	EN50091-2 Approved
	Contact Closure, RS-232/485	Supports MEGATEC RUP, MEGATEC RUPSII, UPSilon 2000 UPS monitoring software
<b>Environment</b>	Operating Temperature	0° – 40° C
	Humidity	0 - 90% Non-condensing
	Audible Noise	< 65 dB at 1 meter
<b>Dimensions</b>	W x H x D (mm)	550*1,600*800
	W x H x D (in)	21.7*63.0*31.5
<b>Weight *</b>	Kilograms	700.0
	Pounds	1,543.2
<b>Battery</b>	Type - Quantity	26AH - 29 ea.
<b>Backup Time **</b>	Minutes - Minimum	5 min.
<b>Battery Cabinet Dim.</b>	W x H x D (mm)	550*1,600*800
	W x H x D (in)	21.7*63.0*31.5
<b>Battery Cabinet Weight</b>	Kilograms	142.0
	Pounds	313.1
<b>Battery Weight</b>	Kilograms	268.0
	Pounds	591.6

\* Weights based on 220/380V IN and OUT. Weights may vary based on input/output frequency/voltage

\*\* Longer backup times (to 8 hours) are available from standard models; custom specifications also available.