



The Frequency Converter People Since 1950

# GEORATOR Corporation

9617 Center Street  
Manassas, VA 20110

800 523-9938

703 368-2101

Fax: 703 368-1078

E-Mail: sales@georator.com

Triathlon III UPS Specifications - 3 Phase Input to 3 Phase Output Model, 270 KVA		
Model		<b>T3UPS-33-270K</b>
Capacity		270 KVA
<b>Input</b>	Voltage (select one individual voltage)	3 Phase Delta 220/380/460 ± 20% 3 Phase Wye 190/200/208/220/230/240V ± 20% 3 Phase Wye 380/400/415/440/460/480V ± 20%
	Frequency (select one)	50 or 60 Hz ± 5% (Optional 400Hz)
	Power Factor	≥ 0.97
	Power Walk In	0-100%: 20 seconds
<b>Output</b>	Voltage (select one individual voltage)	3 Phase Delta 220/380/460V (+/-5% adjustable) 3 Phase Wye 190/200/208/220/230/240V (+/-5% adjustable) 3 Phase Wye 380/400/415/440/460/480V (+/-5% adjustable)
	Voltage Regulation	± 1% at Linear Load
	Phase Shift (unbal. load)	< 0.5 Deg.
	Frequency (select one)	50 or 60Hz ±0.1 Hz (Optional 400 Hz)
	Power Factor	0.8
	Distortion (THD)	< 2.0% (Linear Load)
	Crest Factor	3:1
	Overload Capacity	125% for 15 Minutes, 150% for 10 Minutes, > 150% for 1 Minute
Efficiency	≥ 95%	
<b>Indicators</b>	LCD	Real Time Status, Data or Historical Events, Parameters, Real Time Clock, Inverter & Alarm
	LED	Up to date information (Status) to the User & Audible Alarm
<b>Protection</b>	Over/Under Voltage	Alarm
	Output Short Circuit	Auto-shutdown
	Overload	Auto-shutdown 25 sec. later
	Over Temperature	Auto-shutdown
	Surge	Surge and Lightning Protection
	EMI/EMC	EN50091-2 Approved
<b>Interface</b>	Contact Closure, RS-232	Supports MEGATEC RUP, MEGATEC RUPSII, UPSilon 2000 UPS monitoring software
<b>Environment</b>	Operating Temperature	0° – 40° C
	Humidity	0 - 90% Non-condensing
	Audible Noise	< 65 dB at 1 meter
<b>Dimensions</b>	W x H x D (mm)	2,200*1,600*800
	W x H x D (in)	86.6*63.0*31.5
<b>Weight *</b>	Kilograms	2,900.0
	Pounds	6,393.4
<b>Battery</b>	Type - Quantity	75AH - 87 ea.
<b>Backup Time **</b>	Minutes - Minimum	10 min.
<b>Battery Cabinet Dim.</b>	W x H x D (mm)	3,300*1,600*800
	W x H x D (in)	129.9*63.0*31.5
<b>Battery Cabinet Weight</b>	Kilograms	798.0
	Pounds	1,759.3
<b>Battery Weight</b>	Kilograms	2,322.9
	Pounds	5,121.1

\* Weights based on 220/380V IN and OUT. Weights may vary based on input/output frequency/voltage

\*\* Longer backup times (to 8 hours) are available from standard models; custom specifications also available.